



# TOOLS CHECKLIST

Please make sure you have the items listed below prior to starting the job.

## 1. MATERIALS

- Visquine (6 mil x 12' W x 100' L roll - placed on top & bottom)
- 2" tape to hold foam to PCC
- Foam edge protection (1/4" x 8" W x 100' L roll)
- Wood or round metal stakes
- Cold patch (approx. 20 bags or enough to repair base and shoulder)
- Curing compound
- 2" x 6" board to form up shoulder if AC is damaged
- Grease (for thermometer)
- Replacement pavement markers
- Plywood or carpet

## 2. TOOLS

- Rock drill (1 1/2 - 2" depending on size of pin)
- Round & square point shovels
- Hudson sprayer (for curing compound)
- Cleaning brushes
- Push brooms for traction grooves & clean up
- Hammer & nails
- Wheel barrows
- Utility knife
- Rubber boots
- Rubber gloves
- Single jack to drive pin in
- Hand or power saw
- Dust pan
- Chain

## 3. CONCRETE TOOLS

- 2' x 4' x 14' aluminum hand screed *or*
- 2' x 6' x 14' wood hand screed (straight, not bowed)
- Concrete vibrator
- Concrete edger trowels
- 3' to 4' Bull floats with extension poles
- Flat trowels
- Concrete thermometer
- Slab cutter & extractor
- Concrete saw

## 4. STORM WATER REQUIREMENTS

- 100 gal. container for containment during clean up
- 6 mil visquine to line bottom of container
- Adequate water supply for clean up and all other activities
- Reading of BMP during tailgate safety meeting
- Shop Vac to clean up PCC slurry
- Small trailer for clean out, or two 55 gallon barrels

## 5. EQUIPMENT

- 14' rolling vibrating screed (if available)
- Gradall forklift
- Loader
- Concrete truck with 4 - 5 slump mix
- Small roller
- Vibrator plate
- Lights (night work)
- Generator