

DIGEST OF REVISIONS

2010 STANDARD PLANS ERRATUM NO. 5

October 19, 2012

GENERAL

For the 2010 edition Standards, Revised Standard Plans are new or revised standard plans. This was changed to be consistent with the definition for Revised Standard Specifications.

The listed Revised Standard Plans (RSPs) supersede the comparable standard plans in the 2010 edition Standard Plans book or supplement the 2010 edition Standard Plans book.

PLAN SPECIFIC

PLAN No.	CHANGES
RSP A24C	Added Shared Roadway Bicycle Marking.
RSP A77C5 RSP A77C6 RSP A77C7 RSP A77C8 RSP A77C9 RSP A77C10 RSP A78C3 RSP A78C4 RSP A78C5 RSP A78C6	The components of landscape fabric and grout were eliminated and replaced with a crash-tested, minor concrete mix custom designed for vegetation control under metal beam guard railing and thrie beam barrier, plus an expanded polystyrene foam block-out material to be placed around the posts. The total thickness of the minor concrete (vegetation control) section is 2". Around the post, the block-out material is 1 1/2" thick, with 1/2" minor concrete over it. This new approach reduces the construction cost.
RSP A85B	Changed "Plan of Roadway - Underpass" subtitle to "Plan of Roadway - Overcrossing" Changed "Plan of Roadway - Overpass" subtitle to "Plan of Roadway - Undercrossing"
RSP A86D	This new standard plan provides addition details for barbed wire and wire mesh fence, including standard wire fencing practices as to splices and wrapping wire around posts.
RSP P13	In the Chair Detail, changed the clip wire size from W5 to W2 and the chair wire size from W2 to W5. In the #6 Bar Clip Detail, changed the clip wire size from W5 to W2. Added Note 4.
RSP D73	In the Type G3 plan view, revised the left "T" dimension line to be consistent with Section D-D.
RSP B15-6	In the H=6'-4" Thru H=10'-4" Typical Section, deleted the dimension for High Strength Masonry.