

# DRISI

CALTRANS DIVISION OF RESEARCH,  
INNOVATION AND SYSTEM INFORMATION

# Research

# Notes

Geotechnical/  
Structures

DECEMBER 2023

Project Title:  
Evaluation of Soil Plug Geotechnical  
Resistance in the Design of CISS Piles

Task Number: 3982

Start Date: March 1, 2022

Completion Date: September 30,  
2025

Task Manager:  
TM Liao,  
Senior Transportation Engineer  
David.liao@dot.ca.gov

## Evaluation of Soil Plug Geotechnical Resistance in the Design of CISS Piles

This research will evaluate various soil plug thicknesses and assess their impact on the geotechnical resistance.

### WHAT IS THE NEED?

The California Amendments to AASHTO LRFD Bridge Design Specifications require a design procedure by the American Petroleum Institute (API, 2000) for the design of Cast-In-Steel Shell concrete (CISS) piles larger than 18-inch in diameter. The use of the soil plug in the API design procedure doesn't correspond well with Caltrans practice of cleaning out the soil and backfilling with concrete and steel reinforcement. This research will evaluate various soil plug thicknesses and assess their impact on the geotechnical resistance of the pile and how it correlates with the API design procedure.


### WHAT ARE WE DOING?

Drive three 36-inch diameter test piles with 8 reaction piles to specified tip elevations. The three test piles will be instrumented with vibration wire strain gauges and distributed fiber optic strain sensors. Three stages of static load tests will be performed:

- i. load the test piles to the specified nominal resistance after driving and before removal of the soil plug. (suggest a waiting period, say 5 days after driving before loading the piles)
- ii. remove the soil plug inside the three test piles to a specific depth for each test pile. The remaining soil plug thickness inside the CISS piles will be a function of diameter (e.g. 4D, 6D, 8D) for each load test. Load the test piles to the specified nominal resistance.
- iii. place seal course on the top of soil plug, let set to specified time, then place concrete up to the pile cutoff for all three test piles, load the test piles to the specified nominal resistance and/or geotechnical failure.



DRISI provides solutions and  
knowledge that improves  
California's transportation system



From the measurement data, the shaft and base soil-pile interaction diagrams will be developed at different stages of construction. The level of uncertainty for each stage will be examined. Such data will be used to assess how the actual performance correlates with the API procedures.

### WHAT IS OUR GOAL?

The objectives of this research are as follow:

- a. Evaluate the soil plug contribution to the geotechnical resistance of the pile for variable thicknesses of soil plug.
- b. Evaluate the Caltrans practice of placing concrete and steel reinforcement on top of the soil plug and its effect on the geotechnical resistance of the pile.
- c. Evaluate the API design procedure in predicting the geotechnical capacity of the CISS pile.

### WHAT IS THE BENEFIT?

The research will address the uncertainty and reduce the geotechnical risk that exists when designing CISS piles. The CISS pile foundation is the most expensive foundation that geotechnical designers can recommend because it uses both a thick steel, driven shell that is backfilled with concrete and steel reinforcement. It is used commonly when large lateral pile capacity is required to resist seismic forces. There have been a number of Caltrans projects where the calculated geotechnical resistance was not met during construction due to uncertainty in the design method, and costly change orders were required. The research will help refine and better predict the geotechnical resistance of the soil plug and therefore yield more cost-effective designs with less risk.

### WHAT IS THE PROGRESS TO DATE?

Started driving test piles in May of 2024.