



NOTE:

On overhead mounted signs, with lighting and catwalks, bottom border shall be omitted.

NOTE:

For destinations on lines 1 & 3 use 6 & 4½ (G77-4), 8 & 6 (G77-5) or 10.67 & 8 (G77-6).

ALL DIMENSIONS ARE IN INCHES.

G77 SUFFIX	SIZE	BORDER WIDTH	MARGIN WIDTH	LETTER SIZE, SERIES & STROKE WIDTH					COR. RAD.
				LINE 1	LINE 2	LINE 3	LINE 4	LINE 5	
-4.1	Var x54	1	-	6 CAP	8 NUM	6 CAP			6
-5.2	Var x72	1¼	-	8 CAP	10 NUM	8 CAP			6
-6.1	Var x84	1½	-	10 CAP	10 NUM	10 CAP			12

G77 SUFFIX	SIZE	DIMENSIONS											
		A	B	C	D	E	F	G	H	I	J	K	L
-4.1	Var x54	6	6										
-5.2	Var x72	8	8										
-6.1	Var x84	10	9½										

Green BACKGROUND WITH White BORDER & SYMBOL Reflective message & border
 REFER TO STANDARD ARROW SHEET & POST SPACING TABLE.

APPROVED: [Signature] 11/15/71 7/15/73 10/19/73
 TRAFFIC ENGINEER DATE REVISION