





#### MAY 2024

Project Title: Gravel-Bed River Assessment Tool for Improved Resiliency of Engineering Design

Task Number: 3286

Start Date: September 4, 2019

Completion Date: September 30,

Task Manager: Akber Ali Transportation Engineer (Civil) akber.ali@dot.ca.gov

## Gravel-Bed River Assessment Tool for Improved Resiliency of Engineering Design

Widely available methods for assessing channel dynamics and hazards are based on sand-bed rivers, like the Mississippi River, that do not apply to gravel-bed rivers found throughout the United States. This study will determine the gravel-bed river assessment tool that accounts for changes in gravel-bed rivers from glacial melt and extreme flooding associated with projected future climate change.

#### WHAT IS THE NEED?

The world's rivers and streams are adjusting to changes in climate. In Washington State, stream channels are becoming more dynamic – especially in the vicinity of gravel-bed rivers. Federal, state, tribal, and private roads are increasingly compromised or destroyed due to progressively more dynamic channel processes.

A river's bedload (sediment transported along the channel bed) drives how rivers move into or away from road infrastructure. In order to design durable roads and bridges, California Department of Transportation (Caltrans) needs high quality information on how the natural material in the river system will move and deposit in the vicinity of road infrastructure.

Widely available methods for assessing channel dynamics and hazards are based on sand-bed rivers, like the Mississippi River, that do not apply to gravel-bed rivers found throughout the United States. Caltrans need a gravel-bed river assessment tool that accounts for changes in gravel-bed rivers from glacial melt and extreme flooding associated with projected future climate change.



DRISI provides solutions and knowledge that improves California's transportation system



Gravel-Bed River Assessment Tool for Improved Resiliency of Engineering Design

# Research Notes

In this pilot, Washington State Department of Transportation (WSDOT) proposes to develop practical guidance and methods for assessing bedload transport in gravel-bed rivers for more resilient road infrastructure. This guidance will inform engineering design, hazard assessment, and maintenance strategies of roads along or near gravel-bed rivers.

Other federal and state agencies support the pilot and are willing to assist in the development and review process. WSDOT anticipates that US Forest Service, US Fish and Wildlife Service, Oregon DOT, Caltrans and other public works agencies will use the gravel-bed assessment tool developed by this pilot project.

#### WHAT ARE WE DOING?

WSDOT will test the sediment transport modeling capabilities of the Sedimentation and River Hydraulics Two-Dimensional model (SRH-2D), now the preferred hydraulic modeling software by Federal Highway Administration (FHWA), and compare the results obtained from current FHWA Guidance Hydraulic Engineering Circular (HEC-)18. The pilot study will also consider future extreme weather conditions using the methods described in HEC-17.

The pilot will closely examine the state-of-art technology for collecting direct and indirect measurements of bedload (e.g., passive and active hydroacoustic, Acoustic Doppler Profiler, Apparent Bedload Velocity, photosieving, accelerometers, Passive Integrated Transponder tags, remote sensing, and geographic information system).

WSDOT's hydraulics staff have experienced many challenges in collecting physical bedload samples: it is often dangerous and untenable. Advancements in data collection techniques offer opportunities for indirect measurement of bedload while ensuring safety of DOT staff and contractors. These data could greatly improve the calibration – and therefore the results – of sediment transport models within acceptable limits of accuracy

Physical sampling of bedload (for calibrating sediment transport models) will be compared to data obtained from modern tools in data collection in three case studies. The outcomes will be applied towards guidance development. The goal is to identify data collection techniques that refine inputs into sediment transport models within acceptable limits of accuracy when field-based site calibration is unsafe or untenable.

#### WHAT IS OUR GOAL?

The goal is to identify data collection techniques that refine inputs into sediment transport models within acceptable limits of accuracy when field-based site calibration is unsafe or untenable.

#### WHAT IS THE BENEFIT?

The pilot will conduct three case studies in order to develop the guidance and test methods with a focus on:

- Stream Simulation culvert design for fish
  passage and geomorphic stability, particularly
  in dynamic settings such as alluvial fans and
  transitions of channel slope or confinement.
- Design criteria for bridge and roadway projects at risk from channel migration and spatiallyextensive bed scour or gravel accumulation.
- Design of bank stabilization projects in a manner that maintains integrity of habitat and adjacent streambanks.

#### The key benefits are:

- Maintenance strategies for DOT infrastructure in rivers and streams, such as reconfiguring culverts on small creeks to prevent blockage from heavy aggradation that requires annual dredging.
- Advancements in data collection techniques offer opportunities for indirect measurement of bedload while ensuring safety of DOT staff and contractors.

The contents of this document reflect the views of the authors, who are responsible for the facts and accuracy of the data presented herein. The contents do not necessarily reflect the official views or policies of the California Department of Transportation, the State of California, or the Federal Highway Administration. This document does not constitute a standard, specification, or regulation. No part of this publication should be construed as an endorsement for a commercial product, manufacturer, contractor, or consultant. Any trade names or photos of commercial products appearing in this document are for clarity only.



Gravel-Bed River Assessment Tool for Improved Resiliency of Engineering Design



 Following the completion of the three case studies, WSDOT will prepare the guidance document. The final product of the pilot study will be the publication of WSDOT's guidance and methods. These will be applicable to state DOTs and other highway asset managers across the nation wherever gravel-bed rivers are found.

### WHAT IS THE PROGRESS TO DATE?

Methow River Case Study:
Substantial progress has been made getting an initial hydraulic model up and running for executing the sediment transport module. The existing conditions terrain is nearly completed with progress on other scenarios. The contract with United States Geological Survey(USGS) was extended for another winter for the last opportunity to sample bedload on the Upper Skagit River.

Additional information can be found at: https://www.pooledfund.org/Details/Study/638

The contents of this document reflect the views of the authors, who are responsible for the facts and accuracy of the data presented herein. The contents do not necessarily reflect the official views or policies of the California Department of Transportation, the State of California, or the Federal Highway Administration. This document does not constitute a standard, specification, or regulation. No part of this publication should be construed as an endorsement for a commercial product, manufacturer, contractor, or consultant. Any trade names or photos of commercial products appearing in this document are for clarity only.