



Caltrans Division of Research,
Innovation and System Information

Research

Notes

Transportation
Safety and
Mobility

JANUARY 2021

Project Title:
Connected and Automated (CAV)
Vehicle Application Development

Task Number: 3427

Start Date: January 1, 2020

Completion Date: April 1, 2021

Task Manager:
Pradeepa Pannirselvam
Transportation Engineer (Electrical)
pradeepa.pannirselvam@dot.ca.gov

Software and Hardware Systems for Autonomous Smart Parking Accommodating both Traditional and Autonomous Vehicles

Develop a solution for parking congestion integrated with
autonomous vehicles

WHAT IS THE NEED?

Current parking infrastructure suffers from congestion as the number of vehicles circulating in urban areas is growing and expansion is not a cost-effective solution. In parallel, developments in autonomous vehicle technology mean that driverless vehicles are predicted to be in circulation by the 2020s and make up 40% of vehicle travel by the 2040s.

Expected benefits of autonomous vehicle travel include reduced congestion through vehicle sharing and reduced walking distance for passengers who can be dropped off chauffeur-style by autonomous vehicles. However, empty vehicle cruising, or the case in which autonomous vehicles cannot efficiently locate parking and circle instead, can potentially increase congestion. Given that this new technology has the potential to exacerbate existing congestion issues, it is necessary to develop a solution for parking congestion integrated with autonomous vehicles.

WHAT ARE WE DOING?

This project addresses this issue by providing a full-stack solution including sensors to monitor occupancy, Fog systems to perform local data pre-processing, radios to communicate with autonomous vehicles, and cloud-based software to predict occupancy. This solution is divided into 3 main subsystems which include the Parking Tracker Fog System (PTFS), a wireless sensor network and a Cloud-based server.

The PTFS refers to the local Internet of Things module and is equipped with Dedicated Short-Range Communications (DSRC) technology for Vehicle to Vehicle (V2V) and Vehicle to Infrastructure (V2I) communication. It is responsible for generating useful information about occupancy and vehicle classes based on data collected from the wireless sensor network or data directly received from autonomous vehicles over DSRC.



DRISI provides solutions and
knowledge that improves
California's transportation system

For the wireless sensor network, a tested system of MEMSIC IRIS sensor motes equipped with Passive Infrared Sensor (PIRs) will be used because they have demonstrated compatibility with multi-hop networks that allow for sensor connections over a greater distance. To facilitate DSRC between the PTFS and autonomous vehicles, Ettus B210 Software Defined Radios (SDRs) will be used to communicate using the Vehicle-to-everything standard: IEEE 802.11p.

The study's novel contribution to the ongoing issue of parking congestion will be this DSRC solution for integrating autonomous vehicles into Intelligent Transportation Systems. A Cloud-based server is the final subsystem and will be responsible for collecting data across multiple PTFSs to be inputted into a machine learning model trained to predict occupancy in parking structures. To validate the algorithms employed, parking scenarios will be simulated and system performance evaluated in terms of response time and accuracy. DSRC solution will also be evaluated based on criteria including latency and accuracy.

For the first phase of the project focus will be on the development of three subsystems: 1) wireless sensor network, 2) PTFS, and 3) communication through DSRC with software defined radios. To summarize, the major proposed research tasks are the following:

- To develop a wireless sensor network using MEMSIC IRIS sensor motes for mounted ultrasonic sensors and PIRs that has comparable performance to established systems in.
- To develop a Fog computing system, the PTFS, that will aggregate data and use it to classify vehicles and determine occupancy in addition to communicating with autonomous vehicles over DSRC using installed radios.
- To customize the PTFS's software defined radios for connecting over DSRC with autonomous vehicles in V2V and V2I communication

WHAT IS OUR GOAL?

The goal of this project is that this system will:

1. Be scalable and include multiple lots across a metropolitan area,
2. Operate in real time, and
3. Communicate securely with autonomous vehicles over DSRC.

WHAT IS THE BENEFIT?

The results will contribute important information for the design of Autonomous Smart Parking Accommodating both Traditional and Autonomous Vehicles.

WHAT IS THE PROGRESS TO DATE?

The contract was executed on February 5, 2020. The kick-off meeting was held on February 25, 2020. A literature survey on research works engaging in deploying wireless sensor networks in a star and XMesh topologies has been conducted. The circuit for the sensing mote using an ESP32 development board and Light Dependent Resistors sensors for occupancy detection has been implemented. The fog node functionality on a Raspberry Pi 3 module B+ in order to aggregate the occupancy information from the sensing nodes and keep track of the occupancy status throughout the entire parking space has been developed. The AWS IoT framework to facilitate the connectivity between the fog and sensing nodes has been developed. A Hardware-in-the-Loop simulation comprising a simulated environment of a parking space that interacts with a hardware setup of six parking slots with a demo vehicle has been developed. The functionality of the PTFS fog node regarding reserving parking slots, path guidance and tracking occupancy status over different situations in the Hardware-in-the-Loop simulation has been validated. Work is in progress with Software-Defined Radios (SDR) to integrate the DSRC communication technology within the system.