

Maintenance

MAY 2026

Project Title: Deployment and Evaluation of Targeted Warning Messaging System

Task Number: 4294

Start Date: July 15, 2025

Completion Date: June 30, 2026

Task Manager:

Travis Graham
Transportation Engineer
Travis.Graham@dot.ca.gov

DRISI Division Chief:

Prakash Sah, PE
Prakash.Sah@dot.ca.gov

Deployment and Evaluation of Targeted Warning Messaging System

Developing and testing a vehicle-triggered warning system to enhance safety during lane closures.

WHAT IS THE NEED?

The California Department of Transportation (Caltrans) maintenance crews frequently operate in short-duration lane closures where traditional advance-warning signing is limited by time, geometry, or site constraints. Drivers may approach these closures at high speeds and do not always have adequate time to react to workers or equipment in the lane. This creates an elevated risk of rear-end collisions and near misses. A simple, deployable system that provides earlier and more targeted warnings is needed.

Previous Caltrans research (Project 3919) demonstrated a preliminary concept in which a field vehicle detects approaching traffic and automatically triggers a changeable message sign to display a warning message. While the earlier project confirmed feasibility, additional development is required to integrate a more robust communication link, refine hardware selection, and evaluate performance under real maintenance conditions. Task 4294 continues this effort by expanding system integration, improving reliability, and conducting controlled and field evaluations.

This task supports Caltrans' efforts to reduce crashes at active work sites and provide safer operating conditions for maintenance personnel. The task builds directly on the previous work and advances the system toward an operational prototype suitable for potential broader deployment.

WHAT ARE WE DOING?

This research will complete the development and integration of a targeted warning messaging system designed for deployment in temporary highway maintenance lane



DRISI provides solutions and knowledge that improves California's transportation system.

closures. The system uses a vehicle identification module mounted on the advance-warning vehicle to automatically detect approaching traffic in the merging lane. When a vehicle is identified as approaching the closure at an unsafe speed or trajectory, the system will transmit a signal to a portable message board to display a targeted warning message intended to influence driver behavior before reaching the physical taper or truck-mounted attenuator (TMA).

To support this, the research team is finalizing the hardware and software integration between the detection system and the message board controller. The TrafficCalm 6036 message board will be configured and its Application Programming Interface (API) customized to allow real-time, automated message activation. Point-to-point wireless communication options are being evaluated and tested to ensure adequate reliability, latency, and operational range under field conditions.

After completing integration work and confirming system functionality in controlled test environments, the project will conduct pilot testing in active maintenance work zones. These pilot tests will evaluate system performance, message activation timing, communication reliability, and the system's ability to respond to vehicles that engage in unsafe lane-use behavior, such as late merging, rapid approach speeds, or "leapfrogging" toward the closure point. Field observations, operator feedback, and system data will be used to assess overall effectiveness and support refinement of deployment guidance and recommended practices for future Caltrans use.

WHAT IS OUR GOAL?

The goal is to develop and test an integrated, real-time vehicle-triggered warning system capable of enhancing driver awareness during short-duration lane closures. The final deliverable will include system documentation, test results, and recommended implementation practices.

WHAT IS THE BENEFIT?

The system has the potential to improve safety at active maintenance sites by providing targeted warnings to drivers based on actual traffic conditions. Early warning can reduce sudden braking and near-miss incidents, particularly at locations where placement of advance signs is difficult or where workers are exposed for short intervals. The system may also reduce the amount of traffic control equipment required for short operations, minimizing worker exposure during setup and retrieval.

If successful, the system could be adopted for various field activities including debris removal, guardrail repair, sweeping, and minor corrective maintenance. The work supports Caltrans' broader goals for worker safety and more efficient maintenance operations.

WHAT IS THE PROGRESS TO DATE?

The research team has completed major system integration work, including preparation of the trailer-mounted message board, wireless communication between the Video Detection and Ranging (VIDAR) detection unit and the message board, and processing of vehicle detection data through the message board controller.

Controlled testing has been completed at the Advanced Highway Maintenance and Construction Technology (AHMCT) test track. During testing, the VIDAR camera detected vehicles, transmitted data wirelessly, and activated the message board. The team also evaluated message timing, hardware stability, power use, and overall system performance. A second VIDAR camera has also been incorporated to support evaluation of driver behavior after a message is displayed.

Caltrans has reviewed the proposed field deployment concept, including equipment placement and Changeable Message Sign (CMS) messaging requirements. The deployment approach is being modified to use general vehicle-triggered

warning messages. Caltrans and the research team have identified a potential highway lane-closure site and are completing final field coordination for a deployment.

IMAGES



Image 1: Prototype trailer-mounted changeable message sign used for controlled testing of the Targeted Warning Messaging system. (Source: UC Davis AHMCT)