

Pavement

MAY 2025

Project Title:

New Performance Approach to
Evaluate ASR in Concrete [TPF-5(521)]

Task Number: 4396

Start Date: July 24, 2023

Completion Date: December 31, 2028

Task Manager:

Vipul Chitnis
Research Engineer
Vipul.Chitnis@dot.ca.gov

New Performance Approach to Evaluate ASR in Concrete [TPF- 5(521)]

Advancing new test methods and predictive tools for assessing alkali-silica reaction (ASR) susceptibility in concrete mixtures.

WHAT IS THE NEED?

Alkali-Silica Reaction (ASR) is a harmful chemical reaction in concrete that causes expansion, cracking, and long-term durability problems. Traditional ASR test methods are either too slow, inconclusive, or lack the sensitivity to reliably predict ASR risk in field structures. Recent advances by the Turner-Fairbank Highway Research Center (TFHRC) have produced two new test methods: American Association of State Highway and Transportation Officials (AASHTO) TP-144 (T-FAST) for identifying reactive aggregates and AASHTO T 416 (ATT) for determining the alkali threshold (AT) of aggregate combinations. While promising, these methods require validation within performance-based frameworks and real-world mixture designs. There is also a need to better understand how supplementary cementitious materials (SCMs) influence alkali loading (AL) in concrete and to develop practical mitigation strategies when reactive aggregates cannot be avoided.

WHAT ARE WE DOING?

The work is organized into three main tasks:

- **Selection and characterization of aggregates using TFHRC toolkit tests.** Aggregates are tested using AASHTO TP 144 (T-FAST) to identify reactive phases and AASHTO T 416 (ATT) to determine alkali thresholds, both individually and in combined mix designs.
- **Characterization of supplementary cementitious materials (SCMs).** A full chemical analysis of SCMs is conducted using X-ray fluorescence (XRF) and Raman spectroscopy to assess their effects on alkali loading and potential to mitigate ASR in concrete.



DRISI provides solutions and knowledge that improves California's transportation system.

- **Preparation and evaluation of concrete samples.**

Concrete mixtures are batched using selected aggregates, binders, and SCMs. A protocol for preparing samples for scanning electron microscopy (SEM) has been established, with samples collected for ongoing microstructural analysis.

mixes have been collected. A concrete sample preparation protocol for SEM has been established, and two cements with varying alkali contents have been selected for new Alaska concrete mixtures.

WHAT IS OUR GOAL?

The goal of this study is to evaluate a wide selection of concrete mix designs to validate the use of the new AASHTO TP-144-21 (T-FAST) and alkali threshold test (ATT) methods in conjunction with mix design data, cement mill reports, and SCM properties to determine the likelihood of ASR gel formation in concrete.

WHAT IS THE BENEFIT?

Alkali-silica reaction (ASR) is one of the major degradation causes of concrete. This research will substantiate the method of detecting potential ASR in concrete. The results of this study will be used to design an ASR mitigation test like T-FAST. It is necessary to expand T-FAST capabilities to evaluate ASR mitigation strategies. Guidelines for effective mitigation methods to limit the occurrence of ASR in future concrete are required to protect the long-term investment in California.

WHAT IS THE PROGRESS TO DATE?

- **Aggregate selection and testing:** Aggregate characterization is complete using T-FAST and ATT tests. Combined alkali thresholds (ATMx) for 12 concrete mixes from four states (Virginia, Alaska, Connecticut, and North Carolina) have been measured and documented.
- **SCM characterization:** XRF testing has been completed for all SCM samples. Two samples have been embedded in resin, lapped, and polished for Raman spectroscopy.
- **Concrete sample preparation:** Six-month SEM samples from two Pennsylvania concrete

The contents of this document reflect the views of the authors, who are responsible for the facts and accuracy of the data presented herein. The contents do not necessarily reflect the official views or policies of the California Department of Transportation, the State of California, or the Federal Highway Administration. This document does not constitute a standard, specification, or regulation. No part of this publication should be construed as an endorsement for a commercial product, manufacturer, contractor, or consultant. Any trade names or photos of commercial products appearing in this document are for clarity only.