

Geotechnical/ Structures

November 2025

Project Title:

Stochastic-Based Models for Three
Components of Ground Motions for
Seismic Design of Structures

Task Number: 4524

Start Date: June 18, 2025

Completion Date: June 30, 2027

Task Manager:

Kyungtae Kim
Senior Transportation Engineer
kyungtae.kim@dot.ca.gov

Stochastic-Based Models for Three Components of Ground Motions for Seismic Design of Structures

Developing and validating stochastic models for three components of synthetic earthquake ground motions to improve seismic design accuracy.

WHAT IS THE NEED?

This project aims to develop a comprehensive stochastic model capable of generating all three components of synthetic earthquake ground motions—two horizontal and one vertical—to advance seismic design and analysis. The California Department of Transportation's (Caltrans) current synthetic motion generation method is limited to horizontal components. This project will extend and validate the model using updated earthquake records to accurately represent magnitude, duration, and frequency characteristics essential for realistic seismic simulations.

By integrating the new vertical ground motion model into Caltrans' Risk-Based Seismic Design framework, the project will substantially enhance the accuracy and reliability of bridge performance assessments, particularly for complex and long-span structures. Addressing current modeling limitations and establishing correlations between vertical and horizontal motion data will reduce uncertainty, improve design efficiency, and strengthen Caltrans' ability to ensure structural safety under realistic seismic conditions.

WHAT ARE WE DOING?

The project involves developing a stochastic model for generating vertical earthquake ground motions and validating the existing horizontal component models using updated earthquake records since 2010. This work will enhance Caltrans' synthetic motion generation tool, improving the accuracy and reliability of seismic risk assessments and bridge design, particularly for complex and long-span structures sensitive to vertical motions.

The scope of work includes four main tasks. First, a literature



DRISI provides solutions and knowledge that improves California's transportation system.



review will examine existing stochastic modeling methods, Ground Motion Prediction Equations (GMPEs) for vertical components, and horizontal-vertical correlations using the NGA-West2 data. Next, the team will develop and validate synthetic vertical ground motions reflecting recorded spectral characteristics, including high-frequency content and vertical-to-horizontal (V/H) ratios. The horizontal model will be validated against enhanced earthquake databases, and a final report will document the model development, validation process, and recommendations for implementation.

WHAT IS OUR GOAL?

The objective is to develop a method to generate three components of synthetic earthquake ground motions specified by earthquake conditions such as magnitude, duration, and location. This effort includes developing a new stochastic model for the vertical component and validating the effectiveness of the existing model for the two horizontal components by incorporating new ground motion records.

WHAT IS THE BENEFIT?

By developing a comprehensive stochastic model that incorporates both vertical and horizontal earthquake ground motions, Caltrans can improve the accuracy and reliability of seismic risk assessments and bridge design for complex structures, including long-span and seismically isolated bridges. This advancement strengthens public safety, enables more efficient and cost-effective design, reduces uncertainty in structural evaluations, and enhances the overall effectiveness of Caltrans' Risk-Based Seismic Design framework.

WHAT IS THE PROGRESS TO DATE?

The research team is currently conducting a literature review focused on: (1) stochastic process models for earthquake ground motion; (2) GMPEs for vertical ground motions; (3) empirical correlations

between horizontal components and vertical component recorded motions from the NGA-West2 database; and (4) probabilistic seismic design approach using vertical component for bridges.